

STYLE 12

Style 12 is a top quality carbon yarn packing treated with high performance lubricants, corrosion inhibitors and sacrificial metal, reinforced with inconel wire to aid extraction.

Service

Style 12 is suitable for power generation, chemical and petrochemical industries, not recommended for use with strong oxidising agents.

PROPERTY	
pH range	0 to 14
Temperature range	-85 DEG.C to +430 DEG.C
Pressure range	21 Mpa (maximum)
Shaft Speed	12 m/s (maximum)

Availability

The following square section material is available in coils or pre-formed rings.
mm 3.0, 4.0, 5.0, 6.5, 8.0, 9.5, 12.0, 16.0, 19.0, 22.0, 25.0

Head Office: 15/B, Vinod Apartments, Krantiveer Vasant Rao Naik X Lane, Gowalia Tank. Mumbai – 400036 INDIA
Tel.: 91 - 22 - 2389 0904 / 05 **Fax:** 91 - 22 - 2389 0907 **Email:** starflex@starflex.net
visit us at: www.starflex.net

Disclaimer: The datasheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the company in relation to same. The acquisition of additional data may necessitate revision to parts, or all, of this data sheet, and such information will be supplied as it becomes available.

The information given and, in particular, any parameters, should be used for guidance purposes only. The company does not give any warranty that the product will be suitable for the use intended by the customer.