

## STYLE 32

Style 32 is a PTFE yarn packing pretreated with graphite and high temperature lubricants.

### Service

Style 32 is suitable for petrochemical, chemical brewing, paper and pulp industries.

PROPERTY	
pH range	0 to 14
Temperature range	-85 DEG.C to +260 DEG.C
Pressure range	12 Mpa (maximum)
Shaft Speed	18 m/s (maximum)

### Availability

The following square section material is available in coils  
mm 3.0, 4.0, 5.0, 6.5, 8.0, 9.5, 12.0, 14, 16.0, 19.0, 22.0, 25.0

---

**Head Office:** 15/B, Vinod Apartments, Krantiveer Vasant Rao Naik X Lane, Gowalia Tank. Mumbai – 400036 INDIA  
**Tel.:** 91 - 22 - 2389 0904 / 05 **Fax:** 91 - 22 - 2389 0907 **Email:** starflex@starflex.net  
**visit us at:** www.starflex.net

**Disclaimer:** The datasheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the company in relation to same. The acquisition of additional data may necessitate revision to parts, or all, of this data sheet, and such information will be supplied as it becomes available.

The information given and, in particular, any parameters, should be used for guidance purposes only. The company does not give any warranty that the product will be suitable for the use intended by the customer.