

## STYLE 43

Style 43 is combination packing made from lubricated and graphite impregnated PTFE yarn (GFO type) with the corners of the packing reinforced with a lubricated Aramid yarn.

### Service

Style 43 is suitable for sealing against water, sewage, oils, alkalis, acid and also in wastewater treatment plants.

PROPERTY	
pH range	2 to 12
Temperature range	-85 DEG.C to +260 DEG.C
Pressure range	35 Mpa (maximum)
Shaft Speed	20 m/s (maximum)

### Availability

The following square section material is available in coils  
mm 3.0, 4.0, 5.0, 6.5, 8.0, 9.5, 12.0, 14.0, 16.0, 19.0, 22.0, 25.0

**Head Office:** 15/B, Vinod Apartments, Krantiveer Vasant Rao Naik X Lane, Gowalia Tank. Mumbai – 400036 INDIA

**Tel.:** 91 - 22 - 2389 0904 / 05 **Fax:** 91 - 22 - 2389 0907 **Email:** starflex@starflex.net

**visit us at:** www.starflex.net

**Disclaimer:** The datasheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the company in relation to same. The acquisition of additional data may necessitate revision to parts, or all, of this data sheet, and such information will be supplied as it becomes available.

The information given and, in particular, any parameters, should be used for guidance purposes only. The company does not give any warranty that the product will be suitable for the use intended by the customer.